



Valentine Ladders & Towers

ESTABLISHED 1959

A member of the ATRICK group

Unit 4K,
Ballymount Cross Industrial Estate
Dublin 24.

Tel: 01-4500 150 / 4500 153

Fax: 01-4500 650

Email: info@valentineladders.ie
www.valentineladders.ie

775SERIES

150kg

LOAD CAPACITY

(Load includes user, tools, materials, etc)

115kg

DUTY RATING



BS EN131

STYLE: Fibreglass Trade Extension Ladder



Exclusive Alfio rung joint means Twist-Proof performance

ALFLO rung joints offer Twist Proof performance

Slip-resistant 'D' rungs for comfort and security

Manual thumb operated locking catch

Semi-automatic Locks

Slip-resistant articulated feet for maximum ground contact

Non-conductive fibreglass stiles, ideal for working around electricity

Suitable for trade use

Model 77525

Heavy duty interior rope pulley for easy and safe operation

Moulded foot brace provides enhanced bracing strength and increased protection against damage

SPECIFICATIONS

Product Code	Rungs	Closed Height	Open Height	Reach Height*	Weight
77525	2 x 8	2.45m (8'0")	3.90m (12'10")	4.48m (14'8")	14.5kg
77531	2 x 10	3.03m (9'11")	5.06m (16'7")	5.60m (18'4")	17.2kg
77535	2 x 12	3.61m (11'10")	6.22m (20'5")	6.72m (22'1")	20.1kg
77539	2 x 13	3.90m (12'10")	6.80m (22'4")	7.28m (23'11")	24.7kg
77545	2 x 15	4.48m (14'8")	7.96m (26'1")	8.40m (27'7")	28.4kg

*Based on 1.75m (5'9") as the average reach height of a person.